

DS-2CD2625FWD-IZS

2 MP WDR Vari-focal Network Bullet Camera



## Key Features

- 1/2.8" Progressive Scan CMOS
- 1920 × 1080 resolution
- H.265, H.265+
- 120dB WDR
- IP67, IK10
- BLC/3D DNR/ROI
- Smart encoding: Support low bit rate, low latency
- 4 behavior analyses and face detection

## Specifications

| <b>Camera</b>               |                                                                                                                                  |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor                | 1/2.8" Progressive Scan CMOS                                                                                                     |
| Min. Illumination           | Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR<br>Color: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR                            |
| Shutter Speed               | 1/3 s to 1/100,000 s                                                                                                             |
| Slow Shutter                | Support                                                                                                                          |
| Day & Night                 | IR Cut Filter                                                                                                                    |
| Digital Noise Reduction     | 3D DNR                                                                                                                           |
| WDR                         | 120dB                                                                                                                            |
| 3-Axis Adjustment           | Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°                                                                             |
| <b>Lens</b>                 |                                                                                                                                  |
| Focal length                | 2.8 to 12 mm                                                                                                                     |
| Aperture                    | F1.4                                                                                                                             |
| FOV                         | Horizontal field of view: 105° to 35°<br>Vertical field of view: 56° to 20°<br>Diagonal field of view: 126° to 40.5°             |
| Lens Mount                  | Ø14                                                                                                                              |
| <b>IR</b>                   |                                                                                                                                  |
| IR Range                    | Up to 50 m                                                                                                                       |
| Wavelength                  | 850nm                                                                                                                            |
| <b>Compression Standard</b> |                                                                                                                                  |
| Video Compression           | Main stream: H.265+/H.265/H.264+/H.264<br>Sub stream: H.265+/H.265/H.264+/H.264/MJPEG<br>Third stream: H.265+/H.265/H.264+/H.264 |
| H.264 Type                  | Main Profile/High Profile                                                                                                        |
| H.265 Type                  | Main Profile                                                                                                                     |
| Video Bit Rate              | 32 Kbps to 16 Mbps                                                                                                               |
| Audio Compression           | G722.1/G711ulaw/G711alaw/G726/MP2L2                                                                                              |
| Audio Bit Rate              | 32 to 128kbps                                                                                                                    |
| <b>Smart Feature-set</b>    |                                                                                                                                  |
| Behavior Analysis           | Line crossing detection, intrusion detection, unattended baggage detection, object removal detection                             |
| Face Detection              | Support                                                                                                                          |
| Region of Interest          | Support 1 fixed region for each stream                                                                                           |
| <b>Image</b>                |                                                                                                                                  |
| Max. Resolution             | 1920 × 1080                                                                                                                      |
| Main Stream                 | 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280×720)<br>60Hz: 30fps (1920 × 1080, 1280 × 960, 1280×720)                               |
| Sub Stream                  | 50Hz: 25fps (640 × 360, 352 × 288)<br>60Hz: 30fps (640 × 360, 352 × 240)                                                         |
| Third Stream                | 50Hz: 25fps (1920 × 1080, 1280×720, 640 × 360, 352 × 288)<br>60Hz: 30fps (1920 × 1080, 1280×720, 640 × 360, 352 × 240)           |
| Image Enhancement           | BLC/3D DNR                                                                                                                       |
| Image Setting               | Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or web browser                            |

|                               |                                                                                                                                             |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Day/Night Switch              | Auto/Schedule/Triggered by Alarm In                                                                                                         |
| <b>Network</b>                |                                                                                                                                             |
| Network Storage               | Support Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR                                                           |
| Alarm Trigger                 | Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error, Alarm input, Alarm output |
| Protocols                     | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour            |
| General Function              | One-key reset, anti-flicker, three streams, heartbeat, password protection, privacy mask, watermark, IP address filter                      |
| API                           | ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI                                                                                              |
| Simultaneous Live View        | Up to 6 channels                                                                                                                            |
| User/Host                     | Up to 32 users<br>3 levels: Administrator, Operator and User                                                                                |
| Client                        | iVMS-4200, iVMS-4500, iVMS-5200                                                                                                             |
| Web Browser                   | IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+                                                                                          |
| <b>Interface</b>              |                                                                                                                                             |
| Audio                         | 1 input (line in, 3.5 mm), 1 output (3.5 mm), single track                                                                                  |
| Communication Interface       | 1 RJ45 10M/100M self-adaptive Ethernet port                                                                                                 |
| Alarm                         | 1 input, 1 output (max. 12 VDC, 30 mA)                                                                                                      |
| Video Output                  | 1Vp-p composite output (75 Ω/BNC)                                                                                                           |
| On-board storage              | Built-in Micro SD/SDHC/SDXC slot, up to 128 GB                                                                                              |
| SVC                           | H.264 encoding supports                                                                                                                     |
| Reset Button                  | Support                                                                                                                                     |
| <b>Audio</b>                  |                                                                                                                                             |
| Environment Noise Filtering   | Support                                                                                                                                     |
| Audio Sampling Rate           | 16 kHz                                                                                                                                      |
| <b>General</b>                |                                                                                                                                             |
| Operating Conditions          | -30 °C to +60 °C (-22 °F to +140 °F), Humidity 95% or less (non-condensing)                                                                 |
| Power Supply                  | 12 VDC ± 25%, PoE (802.3at)<br>Terminal block for DC input                                                                                  |
| Power Consumption and Current | 12 VDC, 1.2A, max. 14.5W<br>PoE (802.3at, 42.5V to 57V), 0.1A to 0.5A, max. 16.5W                                                           |
| Protection Level              | IP67, IK10                                                                                                                                  |
| Material                      | Metal                                                                                                                                       |
| Dimensions                    | Φ144.13×332.73 mm (Φ5.67"× 13.10")                                                                                                          |
| Weight                        | Camera: Approx. 1890 g (4.17 lb.)                                                                                                           |

## Available Model:

DS-2CD2625FWD-IZS

## Dimensions

